

#### GENERAL

LAMICAPOR 512-15 - 02 is composed of uncalcined muscovite mica paper bonded to glass cloth with epoxy resin binder and Zinc Naphthenate accelerator.

#### APPLICATION

LAMICAPOR 512-15-02 tapes are used for continuous insulation of coils and bars as well as for insulation of robel type bar for VPI application. The use of uncalcined muscovite mica paper bonded with adequate resin produces a tape of sufficient porosity for complete impregnation of insulation layer without air pockets after curing.

#### PRODUCT CHARACTERISTICS:

Characteristics	Unit	Typical Values	Test Method
Thickness	mm	0.15± 0.02	IEC - 60371-2
Total Weight	g/m <sup>2</sup>	197 ± 20	IEC - 60371-2
Resin Content	g/m <sup>2</sup>	14 ± 3	IEC - 60371-2
Mica Paper	g/m <sup>2</sup>	160 ± 15	IEC - 60371-2
Glass Fabric	g/m <sup>2</sup>	23 ± 2	IEC - 60371-2
Accelerator Content	mg/m <sup>2</sup>	480 ± 120	IEC - 60371-2
Porosity	Sec/100 ml	800 (approx)	IEC - 60371-2
Tensile Strength	N/cm	≥ 70	IEC - 60371-2
Breakdown Voltage (min)	KV/Layer	≥ 1.6	IEC - 60371-2

#### SUPPLY:

LAMICAPOR 512-15-02 is supplied in tape form in standard width of 20 and 25 mm. Standard length of the tape roll is 50 mtrs wound on 55mm ID polypropylene spools suitable for hand taping. Tape is also suitable for machine taping can be supplied on 25 mm ID spool with or without notches as per customer requirements.

#### STORAGE & HANDLING INSTRUCTIONS:

LAMICAPOR 512-15-02 must be kept under controlled temperature condition.

#### SHELF LIFE

At standard temperature of 23 ± 5°C - 10 months  
At refrigerated storage of 05°C - 18 months.

#### JOINTS:

The tapes are supplied without joints. However 10% of the rolls may be supplied with one joint.

#### WORK HYGIENE:

While using LAMICAPOR 512-15-02 we recommend to follow the necessary Health & Safety Standards.

Rev. 00 / Issue Date: 11.01.2010

**LIABILITY:** All the above information is based on our own research and experience. We cannot however offer any Guarantee for the information as the manufacturer himself is responsible for any article made with our product. Neither do we accept Liability for any damage which could be caused by the information given hereby

#### Lakshmanan Isola Pvt. Ltd.

Works: Achalu, Ramanagaram 562 159, Karnataka, India Ph +91 80 2727 1266 / 2727 4996 Fax +91 80 2727 1166  
Regd Off: Casa Fina, 5, Primrose Road, Bengaluru 560 025, India Ph +91 80 4112 4001 Fax +91 80 2559 7778